NETWORK SURVEILLANCE

# NETWORK VIDEO SERVER & DAY-NIGHT CAMERA

## FEATURES

- 6 LED ultra compact Day/Night camera
- 350K Pixel VGA 1/3” CMOS sensor
- 2 channel network video server
- LCD display for easy network port ID, Subnet mask and Gateway
- MJPEG compression, Supports 320 x 240 resolution

LOREX™

SEE WHAT YOU’VE BEEN MISSING

# NETWORK VIDEO SERVER & DAY-NIGHT CAMERA

## SPECIFICATIONS

### NETWORK VIDEO SERVER

- 32-Bit RISC CPU inside
- 1MB Flash Memory
- 8MB Dynamic Memory
- Power input at 5.3vDC 1A max
- Operating humidity at 10% to 90%
- Operating temperature at 0 C to 60 C
- Supports USB 2.0 and USB1.1
- Protective housing required for outdoor use.
- Support all USB PC Camera using VIMICRO ZC0301 Plus processor.
- CMOS VGA, resolution at 320x240
- Frame rate of up to 20fps
- MJPEG compression
- Network protocal: HTTP, TCP/IP, UDP, SMTP, PPPoE, DDNS, DNS, SNTP, BOOTP, DHCP, FTP, SNMP

### DAY-NIGHT CAMERA

- 1/3 inch Color CMOS VGA Sensor with 350,000 pixels.
- Infra-Red LED for Night Vision, effective up to 2.0 meters.
- Picture Format: 640x480, 352x288,320x240, 176x144x 160x120 (CIF, VGA), RGB24
- Up to 30fps @ CIG, 10-15fps @ VGA
- USB interface, compliant to USB 1.1
- USB cable length 1.8 meter
- Adjustable Focus Lens
- Focus Distance: 5cm to infinity
- Auto Adjust: White Balance, Exposure, Color/Brightness, Sharpness, Contras, Light Source
- Operating Temperature: 0ºC to +40ºC
- Powered by USB 5V
- Dimensions: 35(W) x 75(H) x 57(D)
- Weight: 150g

**Lorex Thecnology Inc.**

**300 Alden Road, Markham, Ontario L3R 4C1 Canada.**

**3700 Koppers Street, Suite 100 Baltimore, Maryland 21227, USA.**

©2006 Lorex Technology Inc.
As our product is subject to continuous improvement, SVII & subsidiaries reserve the right to modify product design, specifications & prices without notice and without incurring any obligation. E&OE