ACCESSORY WEATHER RESISTANT*

B&W CAMERA KIT

SG7009X

SYSTEM INCLUDES: B&W CMOS CAMERA,
MOUNTING BRACKET AND 57FT. CABLE

Please read Manual before Use!!!

OWNERS MANUAL

FEATURES

- B&W Weather Resistant* Camera
- One-way Audio
- 3.6mm wide angle lens
- Infra-red illuminators ideal for low light viewing

CAMERA INSTALLATION

1) Attach the Camera to the Metal Bracket and tighten the swivel.
2) Connect the supplied cable to the back of the camera.
3) Attach the metal stand to the wall or ceiling where you want to install the camera. Locate a wall stud or ceiling joist and secure bracket using the supplied screws.
4) Connect the other end of the cable to the back of the monitor.

1. Attach the Pedestal using 4 screws.	2. Attach the Camera onto the Pedestal and tighten the thumb screw.
	

NOTE

*** Weather Resistant against dust and light rain. The camera should ideally be placed under an overhang or eves trough.**

TROUBLE SHOOTING

PROBLEM	REMEDY
No Picture	Check the cable for any loose connection
Picture Flickering	Make sure the camera is not facing any direct Light or Sunlight

NOTE

Keep camera installed away from direct sunlight. Also avoid places where humidity is high or unable to protect rain. The mounting bracket must be attached to a structural device such as wall stud or ceiling rafter using suitable fastener.

Technical Specifications:

- Image Device: B&W CMOS Camera
- Lens: 3.6mm
- Resolution: 240 TV Lines
- Illumination: 0.1 LUX @ F2.0 with IR LED
- Shutter Control: Auto 1/60 – 1/100,000
- Power Requirement: powered from monitor via cable
- Operating Temperature: -14°F to + 122°F
- Housing: White
- Dimensions: 2.5” (W) x 3” (D) x 2” (H)
- Weight: 12 oz

Because our products are subject to continuous improvement, SVC reserves the right to modify product Design and Specifications without notice and without incurring any obligation. E & OE.

For more information, please visit our website at www.strategicvista.com