

# 1/4" CCD COLOR VANDALPROOF POLYCARBONATE DOME CAMERA



## SPECIFICATIONS

Image Sensor:	1/4" Interline transfer type Col CCD
Effective Pixels:	510H x 492V (250K)
Scanning System:	525 Lines 2:1 Interlace
Scanning Frequency:	15.734KHz (H), 59.94Hz (V)
Resolution:	330 TV-Lines
Shutter Speed:	1/60 ~ 1/100,000 sec.
S/N Ratio:	More than 48dB (AGC off)
Sync. System:	Internal
Min. Illumination:	<1 LUX (F2.0)
White Balance:	AWB
Video Output:	1.0 Vp-p (75Ω load)
Lens:	Fixed (3.6mm)
Power Supply:	DC12V ± 10%
Power Consumption:	100mA (DC12V)
Operating Temp:	-10 to +45 C / 14 to 113F
Operating Humidity:	90% RH Max.
Diameter:	125mm

## FEATURES

- Polycarbonate housing provides high impact protection against possible vandalism
- Heavy duty all metal base with swivel bracket and tamper proof hardware adds extra protection
- Smoked camera housing provides unobtrusive appearance
- 1/4" CCD Color image sensor with polycarbonate dome housing
- Rotate camera 360° and/or Tilt camera 90° for optimal angle selection
- Built-in automatic back light compensation
- Includes: 1/4" CCD Color Dome Camera, Polycarbonate Dome Housing, a regulated 12V DC power supply and RCA/BNC connector.



SEE WHAT YOU'VE BEEN MISSING

**VQI532R**

[www.strategicvista.com](http://www.strategicvista.com)

**Strategic Vista International Inc.**

300 Alden Road, Markham,  
Ontario L3R 4C1  
Canada.

3700 Koppers Street, Suite 100  
Baltimore, Maryland 21227,  
USA.

©2005 Strategic Vista International Inc.  
As our product is subject to continuous improvement,  
SVII & subsidiaries reserve the right to modify product  
design, specifications & prices without notice and without  
incurring any obligation. E&OE