

Security at Every Angle

Experience a heightened level of security monitoring and the enhanced ability to now monitor large areas with a single security camera. The optical zoom feature provides the ability to focus on fine details like faces or license plates and with rapid panning and tilt speeds, real-time recording of 30 frames per second, continuous 360° rotation, and 4K UHD resolution, this camera is perfect for high traffic areas. Plus never miss capturing any video footage with 24/7 recording capacity when paired a compatible recorder. Change the way you think about large area monitoring and take your surveillance to the next level with this truly all-seeing camera.

Features



4K Ultra HD Resolution

Color Night



olor Night Vision



Motion Detection



High Dynamic Range







Pan Tilt

Zoom



Fast 400deg/sec Panning speed

E881AP



LOREX[®] 4K Ultra HD IP 25× Pan-Tilt-Zoom Camera

with Mount



Picture Perfect

See every detail with superior definition

- · 4K (8MP) Ultra HD resolution, ensuring clear and detailed footage
- · See more with a with up to 66° field of view, depending on the level of zoom desired
- · Record at a real-time 30 frames-per-second, providing smooth and clearer footage







Color Night Vision

See everything clear as day, even at night

- · Experience enhanced nighttime clarity and better video evidence with Color Night Vision²
- Up to 150ft (46m) IR night vision in low light and 98ft (30m) in total darkness³



No Matter the Weather

Maximize coverage with cameras built for any climate

- Weatherproof rated (IP67)
- Operates in temperatures low as -40°F (-40°C) and high as 131°F (55 °C)
- Durable camera housing, designed to withstand harsh weather conditions • Be confident that this micro security camera is capable of looking after
- itself. It is engineered with an IK10 vandal resistant rating meaning its resilient metal housing is made to withstand all types of violent impacts







Pan. Tilt. Optical Zoom

See more, know more with Pan and Tilt Capabilities

- · Get the full picture with the endless 360° Pan range and
- Fast 400°/sec panning speed and tilt capabilities allows the cameras to cover larger areas of your property
- · 25X Optical Zoom through the Lorex App, provides an added level of clarity
- · Program preset viewing points, patterns, scan cycles and tours when connected to a compatible NVR

E881AP

LOREX[®] 4K Ultra HD IP 25× Pan-Tilt-Zoom Camera with Mount

Video Output

Product Specifications

Specification

Specification		Video Output	
Video Transmission	IP	Resolution/Frame rate	Up to 4K (8MP) @ 30fps
Technology		Effective Pixels	H:3840 × V:2160
Image Sensor	8MP/4K 1/1.8" CMOS	HDR	Yes
Video Format	NTSC	Termination	RJ45
Video Compression	H.265/H.264H (Main Stream & Sub Stream)	NightVision	
Optical		Night Vision Range	150ft (46m)/ 98ft (30m)
Viewing Angle (Horizontal)	61.6°- 3.6°	Color Night Vision	Yes
Viewing Angle (Diagonal)	66.6°-4°	General	
Lens/Lens type	5.3-135mm F1.6- F4.0 / Zoom Module	Body Material	Aluminum Alloy
Optical Zoom	25×	Vandal Resistant Rating	IK10
Digital Zoom	Yes ⁵	SD Card Slot	Yes*
Pan/Tilt Capabilities		Power Requirements	PoE Plus (Power over Ethernet Plus Class -802.3at)/24W
Pan / Tilt Range	Pan: 0°–360° endless Tilt: -15° ~ 90°	Power Consumption (max)	1A/24W
Auto Flip	Yes, 180°	Camera Dimensions (W × H)	6.5 × 13" / 331 × 165mm
Continous Rotation	Yes	Camera Weight	11.7lb / 5.3kg
Manual Speed (Maximum)	Pan: 0.1°–300°/s Tilt: 0.1°–200°/s	Operating Temperature	-40°F ~ 158°F /-40°C ~ 70°C
Preset Speed (Maximum)	Pan: 400°/s; Tilt: 300°/s	Humidity	< 95% RH
Presets	300	Model Information	
Patterns	5	E881AP 4K Ultra HD IP	25× PTZ Camera 6-95529-02868-2
Tours	8	Dimensions	
Other PTZ Functions	Auto Scans, Auto Pan		
Camera OSD	Yes	Package	Brown box
Special Features		Package Weight	15.6lb / 7.1kg
Motion Detection	Yes	Package Dimensions (W × D × H)	10.6 × 10.6 × 25.6" / 270 × 270 × 650mm
		Package Cube	1.67 cbf / 0.047cbm

What's in the box



1 × PTZ Camera



1 × Wall Mount





1 × Safety Chain



1 × Installation Kit



Quick Setup Guide

Disclaimers

- Compatible with select Lorex analog HD recorders. For a full list of compatible recorders visit: www.lorex.com/compatibility
 Full color nighttime video typically switches to black & white IR night vision below 1 lux to ensure optimal low-light image quality.
 Stated IR illumination range is based on ideal conditions in typical outdoor night time ambient lighting and in total darkness. Actual range and image clarity depend on the installation location, viewing area, and light reflection/absorption level of an object. In low light, the camera will switch to black and white. 4. Not intended for submersion in water. Installation in a sheltered area recommended.

5. Digital zoom is a function controlled by the connected NVR. For a list of compatible NVRs visit: www.lorex.com/compatibility

6. A Cat5e cable is required to connect to a compatible NVR. Not included.

*A microSD card can be inserted for independent recording. Data can be accessed through the camera using a web browser but will not upload to the NVR or to the cloud for mobile app viewing. Lorex products are designed for consumer and business use only and not for US federal governments, federally-funded projects or contractors subject to NDAA.

E881AP lorex.com

Lorex Corporation 10440 Little Patuxent Parkway, Ste, 300, Columbia, MD 21044, United States © 2022 Lorex Corporation

As our product is subject to continuous improvement, Lorex Technology & subsidiaries reserve the right to modify product design, specifications & prices without notice and without incurring any obligation. E&OE. (21-0128-LOR) 10272022-6