


WIRELESS HD SECURITY CAMERA SYSTEM



LH0414WB, LH04141TC4W, LH04141TC4WP

WIRELESS CONVENIENCE, HIGH DEFINITION QUALITY

Experience crystal clear HD 720p video day or night. No need to run video cables - experience true peace of mind with reliable wireless video you can view anywhere on your smartphone, tablet, PC or Mac.



LH041 Series DVRs



WIRELESS HD SECURITY CAMERA SYSTEM

DVR FEATURES:

- HD 720p recording resolution ¹
- Tablet / smartphone viewing and playback ²
- Lorex Stratus Connectivity 3 step setup ²
- HDMI cable included for simple connection to HDTVs
- Record to included security grade hard drive with no recurring fees
- H.264 video compression offers reduced file size and network strain for remote viewing
- Continuous, scheduled, and motion recording
- Pentaplex operation view, record, playback, back up & remotely control the system simultaneously
- Dual video outputs (HDMI and VGA) to connect multiple monitors
- Advanced mobile apps with live viewing, playback & video recording ³
- PC and Mac compatible
- Instant email alerts with snap shot attachment
- Accurate time stamps with NTP & Daylight Savings Time
- Automatic firmware upgrades over the Internet ensures your system is always up to date ³







LH041 Series DVRs



WIRELESS HD SECURITY CAMERA SYSTEM



WU3624



VIEW YOUR WORLD IN HD 720p

Protect what matters most with wireless cameras featuring high definition 720p resolution. Compliment your home or business security with extended range and flexibility. Save time and money on setup with easy-to-install wireless cameras.



LH041 Series DVRs

WIRELESS SYSTEM FEATURES:

- HD 720p wireless video with H.264 compression ¹
- SignalGuard Technology continuously monitors the wireless signal and automatically reconnects upon detecting low signal strength
- Next generation adaptive Frequency Hopping Spread Spectrum (FHSS) technology greatly reduces conflicts with competing signals
- IR cut filter achieves accurate color reproduction in varying lighting conditions
- Long Range night vision range up to 120ft (37m) / 80ft (28m) ²
- Simple installation. No video cable required ³
- Weatherproof (IP66) camera and power connectors for outdoor or indoor installation ⁴
- High gain antennas provide up to 160ft (50m) indoor / 500ft (152m) outdoor wireless range ⁵
- Vandal resistant camera design with cable pass-through mounting brackets
- Weatherproof receiver can be installed outdoors for improved range



LH041 Series DVRs



WIRELESS HD SECURITY CAMERA SYSTEM

DVR Specifications

SYSTEM

STSIEM	
Operating System	Linux (embedded)
Pentaplex	Simultaneous View, Record, Playback, Backup & Remote Monitoring
Number of Channels	4 channels
Inputs/Outputs	
Video IN	None (wireless)
Video OUT	1 x HDMI, 1 x VGA
VGA OUT	Yes
HDMI	Yes
Audio IN	None
Audio OUT	None
USB Port	2 x USB (one at front and one at back panel)
Alarm IN	Alarm IN not supported
Alarm OUT	Alarm OUT not supported
Video Output Resolution	1920 x 1080 (HDMI), 1440 x 900, 1280 x 1024, 1280 x 720, 1024 x 768
PTZ control	PTZ cameras not supported
Display	
Live Display	1, 4
Live Display Speed	60 NTSC, 50 PAL
System Navigation	USB Mouse, IR Remote Controller
Motion Area Setting	None
Sensitivity levels	3
Firmware Upgrade	Automatic over the Internet & via USB device and Network
User Authority	By user group
Time Synchronization	Auto time sync by NTP server
RECORDING	
Video Compression	H.264
Audio Compression	None
Recording Resolution Setting	NTSC: 1280x720 (720p) PAL: 1280x720 (720p)
Recording Quality Control	3 levels
Recording Schedule	By hour, by day, by recording mode, by motion, by ch
Pre Recording	Max. 10 Secs
Post Recording	Max. 5 Minutes
Reliability	Watch-Dog, Auto-recovery after power failure
Covert Video	No

PLAYBACK	
Playback Channel	1~4 Adjustable
Playback Speed	Variable Max 16x
Playback Players	Backup Player
Search	By time & event
Log Search	Up to 1,0,000 lines for system, configuration changes, motion/alarm detected, account, record and storage
Audio Play	No
STORAGE & ARCHIVE	
Storage	Up to 1 HDD's (SATA)
Maximum Capacity	up to 4TB
Backup Media	USB flash drive & USB external HDD
Backup File Format	H.264 file (AVI generator included)
CONNECTIVITY	
Cloud Connection	Lorex Stratus Connectivity
Supported Operating Systems	Windows™ Mac OSX
Remote Software	Client Software (PC) & Safari (Mac)
Email notification	Text with snapshot
Instant Smart Phone	iPad®, iPhone®, Android™
DDNS	Free Lorex DDNS
System Configuration	Full setup configuration over network
Ports	Programmable by User
Network Protocol	TCP/IP / DHCP / UDP / DDNS / PPPoE
Network Interface	10/100-Base-TX, RJ-45
Network Speed Control	48Kb ~ 8MB/sec.
GENERAL	
Power Consumption	Approx. 10 watts (no HDD included)
Supply Voltage	100VAC-240VAC, 12VDC , 2A, 50/60Hz
Unit Dimensions	11.8" x 8.7" x 2.0" 300mm x 220mm x 50mm
Unit Weight	1 kg / 2.2lbs
Operating temperature	32° ~ 104° F / 0° ~ 40° C
Humidity	10 ~ 90% RH

	RECORDING RESOLUTION (PIXELS) & SPEED (FPS - FRAMES PER SECOND)	
	FPS	720p Mode 1280x720
4ch	Total	52
40	Per channel	13



General

TX Frequency Range	2.400GHz~2.480GHz	
TX Power	16dBm	
Unobstructed Effective Range 165ft (50m) indoor, 500ft (1		
Data Rate	4 Mb/s	
Modulation	GFSK	
Spread Spectrum	FHSS	
Operating Temperature Range	14°F ~ 122°F / -10°C ~ 40°C	

Wireless Camera

Image Sensor Type	1/3" Color CMOS Image Sensor	
Effective Pixels	H: 1280 V: 720	
Image Compression	H.264	
Image Resolution	HD (1280x720)	
Lens	3.6mm F2.0	
Field of View (Horizontal)	72°	
AGC	On	
Power Requirement	12V DC +/- 10%	
Power Consumption	375mA Max with IR LED 160mA Max without IR LED	
Environment Rating	IP66	
IR LED Quantity / Type	18 pieces / 850nm	
Night Vision Range	120ft (37m) / 80ft (28m)	
Built in Auto IR Turn On / Off	CdS Drive Auto IR LED turn On/Off Circuit	
Dimensions (W x D x H)	71 x 223 x 74mm / 2.8 x 8.8 x 2.9" (with antenna and sunshade)	
Weight	0.3kg / 0.6lbs	

Wireless Receiver


RX Sensitivity	-81dBm
Demodulation	GFSK
Data Rate	4 Mb/s
Supported Resolution	HD (1280x720) up to 15 frames per second
Termination	USB
Power Requirement	5V DC +/- 5%
Power Consumption	600mA Max
Operating Temperature Range	14°F ~ 122°F / -10°C ~ 40°C
Dimensions (W x D x H):	139 x 58 x 20mm / 5.5 x 2.3 x 0.8" (with antenna attached)
Weight:	0.1kg / 0.3lbs

Inputs & Outputs





Wireless System:





LH041 Series DVRs



Product Information:

MODEL	CONFIGURATION	PACKAGE	W x D x H Inches & mm	WEIGHT	CUBE	UPC Code
LH0412W	4 ch HD DVR (LH04141T) with 1TB HDD & 2 x Wireless HD Security Cameras (LWU3622)	Universal Retail Box	392mm x 279mm x 285mm/ 15.4" x 11.0" x 11.2"	3.3kg/7.4lbs	0.02cbm / 1.09cbf	6-95529-00463-1
LH04141TC2W	4 ch HD DVR (LH04141T) with 1TB HDD & 2 x Wireless HD Security Cameras (LWU3622)	Universal Retail Box	392mm x 279mm x 285mm/ 15.4" x 11.0" x 11.2"	3.3kg/7.4lbs	0.02cbm / 1.09cbf	6-95529-00448-8
LH04141TC2WP	4 ch HD DVR (LH04141TP) with 1TB HDD & 2 x Wireless HD Security Cameras (LWU3622)	Universal Retail Box	392mm x 279mm x 285mm/ 15.4" x 11.0" x 11.2"	3.3kg/7.4lbs	0.02cbm / 1.09cbf	6-95529-00520-1
LH0414WB	4 ch HD DVR(LH04141T)with 1TB HDD & 4 x Wireless HD Security Cameras (LWU3624)	Brown Box	392mm x 279mm x 285mm/ 15.4" x 11.0" x 11.2"	TBD	0.02cbm / 1.09cbf	6-95529-00462-4
LH04141TC4W	4 ch HD DVR (LH04141T) with 1TB HDD & 4 x Wireless HD Security Cameras (LWU3624)	Universal Retail Box	392mm x 279mm x 285mm/ 15.4" x 11.0" x 11.2"	TBD	0.02cbm / 1.09cbf	6-95529-00449-5
LH04141TC4WP	4 ch HD DVR (LH04141TP) with 1TB HDD & 4 x Wireless HD Security Cameras (LWU3624)	Universal Retail Box	392mm x 279mm x 285mm/ 15.4" x 11.0" x 11.2"	TBD	0.02cbm / 1.09cbf	6-95529-00521-8
DVR INCLUDES	Pre-Installed HDD, HDMI Cable, E *LH04141T - NA Power Adapter		Iower Adapter [*] , Remote Control, Mo E U/UK Power Adapter.	ouse, Quick Setup Gui	de.	
LWU3624 INCLUDES	4 x Wireless Cameras, 6 x Antenna's, 1 x Wireless Receiver, 4 x Power Adapters, Mounting Kit, Quick Start Guides.					
LWU3622 INCLUDES	2 x Wireless Cameras, 4 x Antenna's, 1 x Wireless Receiver, 2 x Power Adapters, Mounting Kit, Quick Start Guides.					

DVR Disclaimers:

1. Compatible with Lorex 720p HD wireless cameras only. Cameras sold separately. For a list of compatible cameras, please visit www.lorextechnology.com/support.

 Requires a high speed Internet connection and a router (not included). An upload speed of 1Mbps is recommended for the best video performance. Up to 3 devices may connect to the system at the same time. For the latest compatibility list check www.lorextechnology.com as new models become available in the market.

3. Both firmware and software must be updated to latest version to ensure remote connectivity. Firmware updates are pushed to the DVR automatically over the Internet. Always update to the latest software (available at www.lorextechnology.com) after upgrading the DVR firmware.

* Number of Channels / Cameras / Accessories / HDD (hard disk drive) capacity may vary by model. Check your package label for specific content information.

All trademarks belong to their respective owners. No claim is made to the exclusive right to use the trademarks listed, other than the trademarks owned by Lorex Technology Inc. We reserve the right to change models, configurations or specifications without notice or liability. Product may not be exactly as shown. Images are simulated.

Wireless Disclaimers:

1. Compatible with Lorex LH050/LH040/LH041 series DVRs only.

2. Stated IR illumination ranges are based on ideal conditions in typical outdoor night time ambient lighting and total darkness. Actual range and image clarity depends on installation location, viewing area and light reflection/ absorption level of object.

3. Camera and receiver requires a wired connection to an electrical outlet (power adaptors included).

4. Not intended for submersion in water. Installation in a sheltered area required.

5. Maximum wireless transmission range. Actual range dependent upon building materials and other obstructions in path of wireless signal. Install receiver outdoors for best performances.

Lorex Corporation, a division of FLIR Commercial Systems Inc.

250 Royal Crest Court Markham, Ontario, Canada L3R 3S1

7055 Troy Hill Drive Elkridge, Maryland 21075 USA www.lorextechnology.com

© 2015 Lorex Corporation

As our product is subject to continuous improvement, Lorex Corporation & subsidiaries reserve the right to modify product design, specifications & prices without notice and without incurring any obligation. E&OE