COLOR WIRELESS SURVEILLANCE SYSTEM
WITH INDOOR/OUTDOOR NIGHT VISION CAMERA

EWT Enhanced Wireless Technology

WiFi friendly

EXPANDIBLE UP TO TWO CAMERAS

FEATURES

- 'EWT' Eliminates Interference From Most Household Devices
- Fast & Easy Installation - Plug Into any AC Outlet
- Receiver Connects to any TV/VCR/DVD Recorder
- Indoor / Outdoor Night Vision Camera
- Built-in Microphone for Listening Ability
- Camera Can be Battery Operated for True Portable Wireless Operation
- Up to 300ft Wireless Transmission Range*
- Night Vision Allows for Low Light Viewing up to 10ft (3m) from Camera**
- Receiver Automatically Switches View Between Cameras***
- Desktop, Wall and Ceiling Mountable

CONNECTS TO ANY TV

*Maximum open space transmission range. Actual range dependent upon building materials and other obstructions in path of wireless signal.
**IR illumination range of 10ft (3m) under ideal conditions. Objects at or beyond this range may be partially or completely obscured, depending on the camera application.
*** Requires Optional 2nd Camera
This product broadcasts over public airways and its video and audio signals may be intercepted without your consent.

LOREX®

LW1001 Series

www.lorexcctv.com

BUSINESS AND HOME SECURITY

COLOR WIRELESS SURVEILLANCE SYSTEM
WITH INDOOR/OUTDOOR NIGHT VISION CAMERA

SPECIFICATIONS

Camera

Imaging Sensor:	1/4" Color CMOS
CMOS Total Pixels:	H:656 V:492 (NTSC)
View Angle:	52° Diagonal
Minimum Illumination:	3.0 Lux F1.5 (IR off) / 0 Lux (IR on)
Transmission Frequency:	910 MHz - CH1, 920 MHz - CH2 (2CH)
Transmission Power:	0 dBm
Modulation Type:	FM
Bandwidth:	10 MHz
Power Source:	+ 9V (DC)
Unobstructed Effective Range:	330 ft. / 100 meters
Night Vision Range:	Up to 10 ft. / 3 meters
Dimensions:	45x115x160mm / 1.8x4.6x6.3"
Weight:	0.3lbs / 140 g
Operating Temperature Range:	14° F ~ 104° F -10° C ~ 40° C

Receiver

Receiving Frequency:	910-920 MHz - 2CH
Intermediate Frequency:	32 MHz
Demodulation Type:	FM
Receiving Sensitivity:	-85 dBm
Power Supply:	9V (DC)
Consumption Current:	90 mA
Unobstructed Effective Range:	Up to 330 ft. / 100 m
Dimensions:	70x120x83mm / 2.8x4.7x3.3"
Weight:	0.3lbs / 120 g
Operating Temperature:	14 F to 104 F /- 10 C to 40 C
Operating Humidity:	85% RH

PRODUCT INFORMATION

UPC:	**LW1001 -** English Package - 7-78597-01001-5 **LW1001F -** Universal Package - 7-78597-21001-9
Package Weight:	0.9kg / 2lb
Package Dimensions:	298mm/11.73"(w) x 81mm/3.19"(d) x 235mm/9.25"(h)
Package Cube:	0.005 cbm / 0.20 cbf

CONTENTS

LW1001	1 x Wireless Receiver 1 x Wireless Camera 2 x 9V DC Power Adapters 1 x Audio/Video Output Cable 1 x Camera Battery Adapter Cable

LOREX®

Lorex Technology Inc.

300 Alden Road, Markham,
Ontario L3R 4C1
Canada.

3700 Koppers Street
Baltimore, Maryland 21227,
USA.

©2009 Lorex Technology Inc.
As our product is subject to continuous improvement, Lorex Technology & subsidiaries reserve the right to modify product design, specifications & prices without notice and without incurring any obligation. E&OE

2-21052009